YANTON®

PROFESSIONAL FM TRANSCEIVER

PROFESSIONAL FM TRANSCEIVER

T-380

OLED HD DISPLAY

Frequency Range

136-174MHZ/400-480MHZ/PMR446

- 2*250/16 Memory Channels
- Single band standby or dual band standby selection
- One key create group, exit group;
- High/Low Power Selective 5W/0.5W
- Scrambler
- Bluetooth (optional)

YANTON®

PROFESSIONAL FM TRANSCEIVER

PROFESSIONAL FM TRANSCEIVER

T-380

- 2*250/16 Memory Channels
- Single band standby or dual band standby selection
- One key create group, exit group;
- High/Low Power Selective 5W/0.5W
- Scrambler
- Bluetooth (optional)

SPECIFICATION

GENERAL	
Frequency Range	VHF: 136~174MHz
	UHF: 400~480MHz/PMR446
Operating Temperature	-20°C~+60°C
Frequency Combination	Phase lock frequency synthesize
Frequency Stability	±2.5ppm
Memory Channel	2×250 Channels
Working voltage	DC 7.4V
Antenna Impedance	50Ω
Operating Mode	Simplex of co-frequency or alien
	frequency
Dimension	125mm×65mm×35mm
Weight	150g (Include Battery Pack)

TRANSMIT PART	
RF Power	0.5-5W
Modulate Mode (W/N)	16KΦF3E,11KΦF3E
Max. Freq. Deviation (W/N)	<5K / <2.5KHz
Remain Wave Radiation	<-60dB
Transmitting Current	≤1300mA
RECEIVE PART	
Sensitivity	<0.25μV(12dB SINAD)
Squelch Sensitivity	<0.20μV
Intermodulation Antijamming	50dB
Audio Power output	500mW
Receiving Current	≤100mA
Squelch Standby	20mA

Notice: Saving your presence, no additional notice will be sent if specification changes because of technology-improving.